

品名规格	镜片数	Size	像素	TTL	EFL	FNO	FOV	MIC	Distort	CRA	螺牙(M)	螺牙(P)	头部直径	深度	Phi /Holder Size
13505A08	5P	1/3.1"	13M	3.9	3.46	2.2	81.5°	6.17	1%	35	M6.5	P0.25			
135009A08	5P	1/3.1"	13M	3.92	3.46	2.2	81.5°	6.17	1%	35	M6.5	P0.25			
13507A11	5P	1/3.1"	13M	4.18	3.57	2	78.2°	6.17	1%	34.6	M6.5	P0.25			
13501B05	5P	1/3.1"	13M	4.45	3.8	2.2	74°	6.17	1%	33.9	M6.5	P0.25			
054012B01	4P	1/5"	5M	3.3	2.6	2.0	68.2°	4	1%	29.4	一体	无			4.47*4.47
125064A01	5P	1/2.9"	12M	4.9	4.04	2.0	75°	6.8	1%	33.9	M6.8	P0.25			
486021	6P	1/2.3"	48M	5.6	4.88	1.9	78.8°	8.3	1%	34.7°	M8.4	P0.2			
135046A01	5P	1/3.1"	13M	4.3	3.5	2.2	80°	6.17	1%	32.2	一体	无	3.8	1.15	6.77*6.63
125015C01	5P	1/2.9"	12M	4.5	4	2.2	78.3°	6.6	1%	33.6	Φ6.47	无			
085084	5P	1/4"	8M	3.92	2.8	2.0	78.1°	4.83	0.89%	32.2	M6	P0.25			
505064	5P	1/2.8"	50M	4.9	4.04	2.0	78°	6.8	1%	35°	M6.8	P0.25			
486016	6P	1/2.3"	48M	5.6	4.88	1.9	78.8°	8.3	1%	33.9	M8.4	P0.2			
085074	5P	1/4"	8M	4.62	2.74	3.3	78.5°	4.8	1%	32.2	M5.9	P0.25			
165081	6P	1/3.1"	16M	4.3	3.5	2.2	80°	6.17	1%	32.2	一体	无	3.74	0.99	7.5*7.5
086035	6P	1/4"	8M	4.66	1.75	2.4	120	4.8	11%	32.2	M6	P0.25			
134010	4P	1/3.1"	13M	4.3	3.8	2.2	75°	6.17	1%	33.9	M6.5	P0.25			
505265A02	5P	1/2.6"	50M	4.9	4.27	1.8	78.8°	7.43	1%	35.4°	M7.5	P0.2			
125090A02	5P	1/2.8"	12M	4.77	4.05	1.8	76.9°	6.8	1%	34.7°	M6.8	P0.2			
505191	5P	1/2.8"	50M	4.77	4.05	1.8	77°	6.8	1%	34.7°	M6.8	P0.2			
084020A01	4P	1/4"	8M	3.6	2.35	1.8	86°	4.8	1%	34.7°	一体	无	3.76	1.34	5.8*5.8
135121	5P	1/2.8"	13M	6.07	7.2	4.0	48°	4.8	1%	25.7°	M6.8	P0.25			
165059	5P	1/3.1"	16M	4.3	3.63	2.4	78°	6.17	1%	33.9	M6.5	P0.25			
165227	5P	1/3"	16M	4.16	3.75	2.2	76.3°	6.1	1.25%	34.7°	一体	无	3.7	0.94	7*7
135027A02	5P	1/3"	13M	4.3	3.7	1.8	78.8°	6.18	1%	35	M6.5	P0.2			
086035B01	6P	1/4"	8M	4.66	1.75	2.4	120	4.8	11%	33.9	M6	P0.25			